

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 3314 (1984): steel clothes lockers - Specification [CED
35: Furniture]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



IS : 3314 - 1984

Indian Standard
SPECIFICATION FOR
STEEL CLOTHES LOCKERS
(*Second Revision*)

UDC 684'453'6'044 [646'8]



© Copyright 1984

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

SPECIFICATION FOR STEEL CLOTHES LOCKERS

(*Second Revision*)

Furniture Sectional Committee, BDC 35

Chairman

SHRI A. BHARADWAJ
207, Golf Links, New Delhi

Members

Representing

SHRI A. M. CHAKI	Calcutta Cabinet Maker's and Furnishers' Association, Calcutta
SHRI R. S. DUGGAL	Engineer-in-Chief's Branch, Army Headquarters, New Delhi
SHRI S. C. GARG (<i>Alternate</i>)	
SHRI I. P. FIGUEROED	Godrej & Boyce Manufacturing Co Pvt Ltd, Bombay
SHRI H. H. JAMSHEDJI (<i>Alternate</i>)	
SHRI T. N. GUPTA	Central Building Research Institute (CSIR), Roorkee
SHRI V. K. AGGARWAL (<i>Alternate</i>)	
SHRI D. B. JAIN	Directorate General of Supplies and Disposals, New Delhi
SHRI O. D. SANGER (<i>Alternate</i>)	
DR M. L. MEHTA	Ministry of Education & Social Welfare, New Delhi
SHRI P. N. MATHUR (<i>Alternate</i>)	
SHRI J. A. PANCHAL	National Institute of Design, Ahmadabad
SHRI H. K. VYAS (<i>Alternate</i>)	
SHRI ASHOK C. PATEL	Chandan Metal Products Pvt Ltd, Vadodara
SHRI ARUN C. PATEL (<i>Alternate</i>)	
SHRI P. RAJAGOPALAN	Indian Institute of Architects, Bombay
REPRESENTATIVE	Small Industries Service Institute, New Delhi
SHRI S. N. SANYAL	Forest Research Institute and Colleges, Dehra Dun
SHRI M. B. SAXENA	Central Public Works Department, New Delhi
ARCHITECT (NZ) VIII (<i>Alternate</i>)	
COL G. B. SINGH	The Indian Plywood Manufacturing Co Ltd, New Delhi
DR A. PURUSHOTHAM (<i>Alternate</i>)	

(*Continued on page 2*)

© Copyright 1984

INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act* (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

Members

SHRI P. B. SHETH

SHRI B. L. SHETH (*Alternate*)

SHRI L. G. TOYE

SHRI V. K. PUNJ (*Alternate*)

SHRI N. VENKATARAMAN

SHRI N. E. GOVINDAN (*Alternate*)

SHRI G. RAMAN,
Director (Civ Engg)

Representing

Ahmedabad Eagle Engineering Enterprises Pvt
Ltd, Ahmadabad

Research, Design and Standards Organization
(Ministry of Railways), Lucknow

The Western India Plywoods Ltd, Distt
Cannanore (Kerala)

Director General, ISI (*Ex-officio Member*)

Secretary

SHRI A. K. AVASTHY
Assistant Director (Civ Engg), ISI

Metal Furniture Subcommittee, BDC 35 : 1

Convener

SHRI J. A. PANCHAL

National Institute of Design, Ahmadabad

Members

SHRI H. K. VYAS (*Alternate to*
Shri J. A. Panchal)

SHRI J. K. AGGARWAL

Engineer-in-Chief's Branch, Army Headquarters,
New Delhi

SHRI M. N. KHULLAR (*Alternate*)

SHRI V. K. AGRAWAL

Hindustan Aluminium Corporation Ltd, Bombay

SHRI ATMA RAM BEHKI

The Small Scale Steel Furniture Manufacturers'
Association (Regd), New Delhi

SHRI SHIV KUMAR KAPAH (*Alternate*)

SHRI I. P. FIGUERO

Godrej & Boyce Manufacturing Co Pvt Ltd,
Bombay

SHRI H. H. JAMSHEDJI (*Alternate*)

SHRI GOPAL RAMNARAYAN

Featherlite Corporation, Bangalore

SHRI BALDEV RAMNARAYAN (*Alternate*)

SHRI D. B. JAIN

Directorate General of Supplies and Disposals,
New Delhi

JOINT DIRECTOR OF INDUSTRIES

AND COMMERCE (RP)

The Director of Industries and Commerce,
(Government of Tamil Nadu), Madras

DEPUTY DIRECTOR OF INDUSTRIES

AND COMMERCE (L C) (*Alternate*)

SHRI ASHOK C. PATEL

Chandan Metal Products Pvt Ltd, Vadodara

SHRI ARUN C. PATEL (*Alternate*)

Indian Standard

SPECIFICATION FOR
STEEL CLOTHES LOCKERS

(*Second Revision*)

0. FOREWORD

0.1 This Indian Standard (Second Revision) was adopted by the Indian Standards Institution on 30 January 1984, after the draft finalized by the Furniture Sectional Committee had been approved by the Civil Engineering Division Council.

0.2 This standard was first published in 1965 and subsequently revised in 1976. In this revision the grades of materials to be used in components have been given.

0.3 This standard contains clause 10 which requires the purchaser to supply certain information at the time of placing orders.

0.4 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS : 2 - 1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard covers the requirements for materials, size, construction and finish of steel clothes lockers with hinged doors.

2. MATERIALS

2.1 Electrodes — The welding electrodes for gas, arc and spot welding shall conform to IS : 1278-1973†, IS : 814 (Part 2)-1974‡ and IS : 4972 - 1968§ respectively.

*Rules for rounding off numerical values (*revised*).

†Specification for filler rods and wires for gas welding (*second revision*).

‡Specification for covered electrodes for metal arc welding of structural steel: Part 2 For welding sheets (*fourth revision*).

§Specification for resistance spot-welding electrodes.

2.2 Mild Steel sheets — Mild Steel sheets shall conform to grade 0 of IS : 1079-1973* or grade 0 of IS : 513-1973†.

2.3 Screws — Screws shall conform to IS : 1365 - 1978‡.

3. TYPES

3.1 Clothes lockers shall be of the following four types (*see* Fig. 1).

- a) 6-locker type,
- b) 8-locker type,
- c) 12-locker type, and
- d) 18-locker type




FIG. 1 DIVISION OF COMPONENTS FOR DIFFERENT TYPES OF CLOTHES LOCKERS

4. DIMENSIONS AND TOLERANCES

4.1 Dimensions — The overall dimensions of clothes lockers shall be as follows:

Height	1 855 mm (excluding pedestal height)
Width	910 mm
Depth	480 mm

NOTE — The minimum clearances required for the clothes lockers to be put into recesses or openings, where required, shall be as follows:

For top	20 mm
For each side	10 mm
For depth	5 mm

*Specification for hot rolled carbon steel sheet and strip (*third revision*).

†Specification for cold rolled carbon steel sheets (*second revision*).

‡Specification for slotted countersunk head screws (*third revision*).

4.2 Tolerances — The overall dimensions specified in 4.1 shall not vary more than ± 5 mm.

5. FABRICATION

5.1 Sides — The sides shall be made from mild steel sheets not less than 0.8 mm thick and without any burrs or dents. The width of the side sheets shall correspond to the depth of the top and shall extend between the extreme surfaces of top and bottom.

5.2 Back — The back shall be made from mild steel sheets not less than 0.8 mm thick and without any burrs or dents. The width of the back sheet shall correspond to the width of the top and shall extend between the extreme surfaces of top and bottom.

5.3 Top and Bottom — The length of the top and bottom shall cover the width and the breadth shall cover the depth. These shall be made from mild steel sheet not less than 0.8 mm thick, and without any burrs or dents.

5.4 Partitions and Shelves — Partitions and shelves for lockers shall be manufactured from mild steel sheet not less than 0.8 mm thick. The joints shall be made by flanging the sheets to a width of at least 15 mm. The arrangement for division of compartment shall be as shown in Fig. 1.

5.5 Doors — Each locker shall be fitted with a flush-fitting single door made from mild steel sheet not less than 0.8 mm thick. The edges of the door shall be bent into a double return at least 12 mm deep and 10 mm wide. Except when the purchaser specifies another type of vent, each door shall be fitted with two louvered vents.

5.5.1 The door shall swing on butt type hinges and shall have a key slot in front at the middle of the height.

5.6 Pedestal — The pedestal shall be made from mild steel sheet not less than 0.8 mm thick and shall be properly stiffened. The height of the pedestal shall be 125 ± 5 mm.

5.7 Hinges — The hinges shall be either plain butt type made from mild steel sheet not less than 1.6 mm thick or double folded type fabricated from mild steel sheet not less than 1.25 mm thick.

5.8 Handle — Each door shall be fitted with mild steel or aluminium handle. The mild steel handle shall be either electroplated or painted. The aluminium handle shall be anodized and the anodic coating shall not be less than grade AC 10 of IS : 1868-1968*. The handle shall be fixed to the door front by means of machine screws or spot welding.

*Specification for anodic coatings on aluminium (*first revision*).

5.9 Lock — This shall be a 5-lever lock conforming to IS : 729 - 1979* or 5-pin cylinder lock.

5.9.1 Six and 8-locker type clothes lockers shall have the internal locking arrangement and 12- and 18-locker type clothes lockers shall either be fitted with a hasp and staple or shall have a built-in hasp and staple arrangement.

6. ASSEMBLY

6.1 The various components shall be assembled by means of screwing, bolting or welding.

6.2 The method of gas welding arc welding and spot welding shall conform to IS : 1323-1966†, IS : 816-1969‡ and IS : 819 - 1957§ respectively.

7. ADDITIONAL ACCESSORIES

7.1 The following additional accessories may be provided if so desired by the purchaser:

- a) *Coat Hooks* — Coat hooks for 6-locker type shall be of mild steel or aluminium and shall be ball pointed; these shall be nickel or chromium plated conforming to IS : 1068-1968|| or anodized in the case of aluminium and fitted in the centre of the underside of the shelf.
- b) *Number Plates* — Lockers shall be provided with polished aluminium number plates with black numerals fixed to the top of door front.
- c) *Hanging Rod* — This shall be of mild steel tubular pipe conforming to IS : 7138-1973¶ or aluminium tubular pipe with a wall thickness of not less than 1.6 mm and 20 mm in diameter. The mild steel hanging rod shall be covered with an aluminium sheet not less than 0.56 mm and in the case of aluminium hanging rod it shall be anodized or buffed. The hanging rod shall be fitted to the lockers with suitable brackets.

8. FINISH

8.1 Steel Sheet Components

8.1.1 All dents, burrs and sharp edges shall be removed from the various components. The components shall be individually pickled, scrubbed and rinsed to remove grease, rust, scale or any other foreign element.

*Specification for drawer locks, cupboard locks and box locks (*third revision*).

†Code of practice for oxy-acetylene welding for structural work in mild steel (*first revision*).

‡Code of practice for use of metal arc welding for general construction in mild steel (*first revision*).

§Code of practice for resistance spot welding for light assemblies in mild steel.

||Specification for electroplated coatings of nickel chromium on iron and steel (*first revision*).

¶Specification for steel tubes for furniture purposes.

8.1.2 Immediately after pickling, all the mild steel parts shall be given phosphating treatment conforming to class C of IS : 3618 - 1966*. The process for application of phosphate coating shall be in accordance with IS : 6005-1970†.

NOTE — Putty shall be applied to all the surfaces requiring filling and shall conform to IS : 110 - 1968‡. Aluminium primer shall conform to IS : 5660 - 1970§.

8.1.3 Coat/coats of enamel paint shall then be applied as follows:

- a) Finish coat with enamels conforming to IS : 151-1950||, IS : 2932-1974¶ or IS : 2933-1975**; and
- b) In case of stoving enamel the components shall thereafter be baked at a specified temperature in an even heated uniformly. The finish shall be smooth and uniform with hard and tough film of enamel strongly adhering to the surface. The finish shall be free from all visible defects and shall not chip when tapped lightly with a dull pointed instrument.

8.2 All other components shall be finished in colour as agreed to between the purchaser and the manufacturer.

9. PERFORMANCE REQUIREMENTS OF FINISH

9.1 Scratch Hardness Test — A sample of mild steel plate 150 × 50 mm in size and thickness 0.315 mm and finished as given in 8 shall be subjected to scratch hardness test in accordance with 15.1 of IS : 101-1964††. A scratch showing the bare metal shall not be produced on the test sample.

9.2 Pressure Test — Samples prepared from mild steel plates of thickness 0.315 mm and finished as given in 8 shall be subjected to pressure test in accordance with 15.2 of IS : 101 - 1964††. The metal surface shall not be rendered visible when the test pieces are separated after the test.

9.3 Flexibility and Adhesion Test — A sample of mild steel plate 150 × 50 mm in size and thickness 0.315 mm and finished as given in 8 shall be subjected to flexibility and adhesion test in accordance with 16 of IS : 101-1964††. The paint film on the test piece shall not show damage, detachment or cracking when examined under ×10 magnification.

*Specification for phosphate treatment of iron and steel for protection against corrosion.

†Code of practice for phosphating of iron and steel.

‡Specification for ready mixed paint, brushing, grey filler, for enamels, for use over primers (first revision).

§Specification for ready mixed paint, brushing, aluminium red oxide primer.

||Specification for ready mixed paint, spraying, finishing, stoving, enamel for general purposes, colour as required.

¶Specification for enamel, synthetic, exterior (a) undercoating, (b) finishing (first revision).

**Specification for enamel, exterior (a) undercoating, (b) finishing (first revision).

††Methods of test for ready mixed paints and enamels (second revision).

9.4 Stripping Test — A sample of mild steel plate 150 × 50 mm in size and thickness 0.315 mm and finished as given in 8 shall be subjected to stripping test in accordance with 17 of IS : 101-1964*. The scratch produced after the test shall be free from jagged edges.

9.5 Test for Protection Against Corrosion Under Conditions of Condensation — A mild steel panel of size 150 × 100 mm and thickness 1.25 mm finished as given in 8 shall be subjected to test for protection against corrosion under conditions of condensation in accordance with 18 of IS : 101-1964*. The metal surface shall show no signs of corrosion after the test.

10. INFORMATION TO BE SUPPLIED BY THE PURCHASER

10.1 The purchaser shall supply the following information to the supplier along with the order:

- a) Type of locker;
- b) Sequence of numbering;
- c) Colour of finish;
- d) Where alternative methods of construction and finish are specified, they shall be clearly stated in order; and
- e) Whether corners to be rounded or not.

11. PACKING

11.1 All the components parts shall be packed in such a way that no damage is caused to them during transit.

12. MARKING

12.1 All steel clothes lockers shall be marked with a suitable mark identifying the manufacturer.

12.1.1 The steel clothes lockers may also be marked with the ISI Certification Mark.

NOTE — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

* Methods of test for ready mixed paints and enamels (*second revision*).

INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

Base Units

Quantity	Unit	Symbol
Length	metre	m
Mass	kilogram	kg
Time	second	s
Electric current	ampere	A
Thermodynamic temperature	kelvin	K
Luminous intensity	candela	cd
Amount of substance	mole	mol

Supplementary Units

Quantity	Unit	Symbol
Plane angle	radian	rad
Solid angle	steradian	sr

Derived Units

Quantity	Unit	Symbol	Definition
Force	newton	N	$1 \text{ N} = 1 \text{ kg.m/s}^2$
Energy	joule	J	$1 \text{ J} = 1 \text{ N.m}$
Power	watt	W	$1 \text{ W} = 1 \text{ J/s}$
Flux	weber	Wb	$1 \text{ Wb} = 1 \text{ V.s}$
Flux density	tesla	T	$1 \text{ T} = 1 \text{ Wb/m}^2$
Frequency	hertz	Hz	$1 \text{ Hz} = 1 \text{ c/s (s}^{-1}\text{)}$
Electric conductance	siemens	S	$1 \text{ S} = 1 \text{ A/V}$
Electromotive force	volt	V	$1 \text{ V} = 1 \text{ W/A}$
Pressure, stress	pascal	Pa	$1 \text{ Pa} = 1 \text{ N/m}^2$

INDIAN STANDARDS INSTITUTION

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110 002

Telephones : 26 60 21, 27 01 31

Telegrams : Manaksanstha

Regional Offices:

		Telephone
Western : Novelty Chambers, Grant Road	BOMBAY 400007	89 65 28
Eastern : 5 Chowringhee Approach	CALCUTTA 700072	27 50 90
Southern : C. I. T. Campus	MADRAS 600113	41 24 42
Northern : B69, Phase VII	S.A.S. NAGAR (MOHALI) 160051	8 78 26

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur	AHMADABAD 380001	2 03 91
'F' Block, Unity Bldg. Narasimharaja Square	BANGALORE 560002	22 48 05
Gangotri Complex, Bhadbhada Road, T.T. Nagar	BHOPAL 462003	6 27 18
22E Kalpana Area	BHUBANESHWAR 751014	5 36 27
5-8-58C L. N. Gupte Marg	HYDERABAD 500001	22 10 83
R14 Yudhister Marg, C Scheme	JAIPUR 302005	6 98 32
117/418 B Sarvodaya Nagar	KANPUR 208005	4 72 92
Patliputra Industrial Estate	PATNA 800013	6 28 08
Hantex Bldg (2nd Floor), Rly Station Road	TRIVANDRUM 695001	32 27